

CONNECTORS AND END CAPS USED FOR DIRECT BURY APPLICATIONS, STRENGTHENED, INSEPARABLE MICRO DBNR/ZDBNR

7-16 mm

Description

Strengthened connectors, disposable, inseparable – for single use after which there is no possibility of disconnection without destroying the microduct. Designed for montage and direct burying underground, with a latch mechanism in the form of a double metal anchoring ring with a very high grip strength.

Straight connector Micro DBNR



(for direct bury applications)

End cap Micro ZDBNR



(for direct bury applications)

Technical specifications

Straight connector Micro DBNR	7	8	10	12	14	16
Outer diameter of microduct [mm]	7,0	8,0	10,0	12,0	14,0	16,0
Pressure resistance [bar]	20					
Impact resistance in temperature-20°C [J]	> 1					
Tensile resistance of the connection [N]	> 500					
Installation temperature range[°C]	- 20 to + 50					

End cap Micro ZDBNR	7	8	10	12	14	16
Outer diameter of microduct [mm]	7,0	8,0	10,0	12,0	14,0	16,0
Pressure resistance [bar]	20					
Impact resistance in temperature-20°C [J]	> 1					
Tensile resistance of the connection [N]	> 500					
Installation temperature range [°C]	- 20 to + 50					