


UNI-TUBE ADSS SINGLE SHEATH CABLE HDPE

2 FIBER G.652D

Outer Sheath HDPE
 PBT Loose Tube-Jelly filled
 SMFiber
 WS Tape
 Aramid Yarn
 Rip Cord



Features

- Single Loose Tube
- Unarmoured construction
- Rip cord to open Outer Sheath
- Non metallic cable
- Water Swellable Tape over the Core
- Aramid Yarn as Peripheral Strength Member
- Small Cable Diameter
- Multiple Network Applications
- PBT Loose Tube filled with Thixotropic Jelly
2,0 mm +/- 0,1mm
- Outer Sheath Black HDPE : Thickness -1,8 mm (Nom)
- Inkjet-Print/Hot-foil : MICRO CABLE, NUMBER OF FIBER,
FIBER TYPE, PRODUCTION CODE, DRUM NUMBER
- Transport : Plywood / Wooden Drum

Technical Data/Norms

Standards :	IEC 60794, EIA/TIA, ITU-T, EN 187000, Telecordia GR-20, RUS 1755.900
Operation/Storage :	-40° to +60°C
Installation :	-40° to +60°C
Fiber type :	Singlemode G.652D, IEC/ITU standards

Cable Type	Fiber Number	Diameter Ø Nom.	Weight Nom.	Tensile Strength Max	Crush Resistance	Impact Resistance	Min. Bending Radius
Single Tube ADSS HDPE 2	2	6,5mm (+/-0,5mm)	35 kg/km	1500N	2000N/100mm	10Nm	20D